



HONEYCOMBED CONTACT FILTER BY PVC & ABS


This contact filter is made with waved open shape of honeycombed structure. It possesses outstanding strength that can bear the lumpy surface and contain a wide and long contact surface with flowing fluid, make it turn to turbulence condition and then reach the highest oxidize rate. This is the epochal product that is the best choice for applying to organic disposal sewage treatment.

FEATURES:

- Larger surface with outstanding treatment function(45-105 m² / m³) .
- Remarkable strength and safe installation operation.
- Little water resistance, high leaking rate(99.0~99.3%), no obstruct produced on contact filter.
- Provided with moderate feature for bio-membrane to adhere to.
- High feature for capturing plankton
- Great mechanical strength, not easy to be out of shape, not easy to get curved, excellent durability.
- Low expense, high efficiency, great economic benefits.



- ⊖ Period of adsorption
- ⊗ Period of growth
- ⊕ Clastic reproducing
- ⊖ Stationary phase
- ⊖ Peel



Specification Model	Aperture (mm)	Effective surface area (m ² / m ³)	Leaking rate (%)	Thickness of single slice	Standard dimension		
					L	W	H
CM-80	80	53	99.2	0.55	1000	500~	1000
CM-56	56	72	99.2	0.5	1000	500~	1000
CM-40	40	105	99.0	0.4~0.45	1000	500~	1000

The specialized heart · environmental protection sentiment ~ is the same management idea.

